

Rolling Shutters

Robust and Reliable in Tough Everyday Operation



Index

Introduction	2
Know-how of Specialists	3
Decotherm CN	4-5
Controls and Accessories	6
Safety Features	6
Overview of Door Types	7

"A Good Reputation Must Be Earned"

August Hörmann, Founder, 1886-1944

Thomas J. Hörmann Martin J. Hörmann Christoph Hörmann



Hörmann, a wholly-owned family enterprise is now run by the 4th generation. The company has prospered by manufacturing expertly crafted and high quality doors for its customers. It has become an internationally active group, securing a leading position in the world market. Hörmann now operates more than 20 highly specialised factories using the most advanced technology to manufacture a wide range of high quality products. Today, as in the past, the name Hörmann is synonymous with uncompromising quality.



Hörmann Beijing Door Production Co., Ltd.

Since its China engagement in 1998, Hörmann Beijing Door Production Co., Ltd. has earned a reputation as a manufacturer of high quality products in Asia. The Beijing factory uses high-tech know-how and stateof-the-art equipment to produce hinged doors, such as fire resistant doors, security doors, fire security doors, internal doors and multipurpose doors, all based on German quality standards. Hörmann Tianjin Door Production Co., Ltd



Hörmann has established in China its second factory in the year of 2008, Hörmann Tianjin Door Production Co., Ltd, to manufacture garage doors, industrial doors and loading technology, such as sectional doors, high-speed doors, rolling shutters, dock levellers and dock shelters, in its new 16000 m² plant in Baodi, Tianjin.

As the world's door producer Hörmann moves its state-of-the-art production closer to customers and allows a rapid response to rising demand.



Schmidhuber + Kaindl GmbH Architektur und Generalplanung / ARGE Deutscher Pavillon Architecture / Consortium German Pavilion

Hörmann is official sponsor of the German Pavilion at the Expo 2010 in Shanghai.



The Reliable Know-How of the Specialist

In-house product development



At Hörmann, new products, further developments and detailed improvements all form part of an ongoing process involving a highly qualified development team. This gives rise to patented products which offer the customer unique benefits. Highly specialized production



Our production systems are based on our own ideas. Applying state-of-the-art technology, we are able to produce industrial doors of a consistently high standard.

All the essential shutter components, such as profiles, side guides, support brackets, fittings, and control technology are developed and produced by Hörmann. At Hörmann quality has a system! Special solutions are our strength



Hörmann's high degree of specialization in rolling shutter construction extends well beyond normal standards.


For our high-performance team, implementing special solutions is part and parcel of their daily agenda. With us you can realise even the most unusual of solutions.



Decotherm CN "Full-Hard" Steel Rolling Shutter

Innovative profile technology


Hörmann has decisively improved its rolling shutters with the high-tech profile. A combination of a thoroughly optimised profile geometry with special steel alloys shows what is possible today in rolling shutter construction.





The concave interior and exterior surfaces of the profiles ensure extremely good roll-up action. Optimally designed hinges reduce heat loss and enable a connection between the curtain and barrel, without the usual pressure and wear marks.






RAL 9002-Standard Colour
RAL 9006-Standard Colour
RAL 9016-Standard Colour
RAL 9016-Standard Colour
RAL 5010-Standard Colour



Window elements

Decotherm CN can be equipped with window elements and ventilation grilles on request. Double-skinned window elements consist of transparent, impact-resistant polycarbonate with high-quality cover frames (similar to RAL 9006). The benefit of these frames:

The PU foam is no longer visible, noise and abrasion are reduced.



Rectangular Logistics arrangement Ventilation grille

Technical data		
Profile type	Decotherm CN	
Material of curtain	Steel	
Standard colours	RAL 9002/9006/9016/5010	
Special colours	•	
Profile height	109 mm	
Curtain weight	approx. 10 kg/m ²	
Wind load *	Class 2	
Thermal insulation	3.8 W/m ² K	
Windows	•	
Ventilation grilles	•	
Max. Width **	8000 mm	
Max. Height **	7750 mm	

* Up to a door width of 8000 mm

(The door will be equipped with wind lock when the door width >5000 mm) ** The max. area of rolling shutter is $40m^2$

Optionally available



- Impulse controls 445R (400V)
- Controls and door leaf components in protection class IP 65 (hose water protected) Connection with a CEE phasechanger plug corresponds to protection class IP 44
- External menu readout via an integral double 7-segment display
- Adjustments are no longer made at the motor but can be conveniently carried out from the control unit via digital limit switches
- Service menu with maintenance, cycles and operating hours counter as well as fault/error analysis
- Function blocking via miniature lock



1-channel receiver unit HEI 1



Pull switch with plastic pull rope Horizontal or vertical installation possible, aluminium die-cast housing IP 65, rope length 4 m.



Hand transmitter HS 4 with 4 buttons



Induction loop DI 2 in a separate additional housing. Suitable for two separate induction loops. Switching capacity: 250 V AC, 4A, 1000 VA Supplied with loop cable



Push-button For separate control of both operational directions, with separate STOP button. 66 x 145 x 68 mm (W x H x D)



Radar infrared presence detector movement and presence detect function. Switch the door quickly and automatically. Protection category IP 65.

Decotherm CN

Controls, Accessories and Safety Features



Integral safety device in direct drive operators The device offers especially good absorption, a large amount of power reserve and reliably prevents the door curtain from falling.



Secure barrel

Dimensioned in accordance with standards (deflection less than 1/500th of the support width). The fixed inner round plate revents fatigue fractures developing on the weld seam or the rivets of the outer round plate.



Side guides and wind locks The articulated design of the wind locks enables the rolling shutter to withstand extreme wind pressure.


Stable side guides are made of galvanised steel.

With a brush seal for quiet travel and tightness.



Safety devices

Closing edge safety device, roll-up safety device and through-traffic photocell are self-testing before and during every shutter cycle. If a fault/ malfunction is detected in just one of the units, the shutter's control system automatically switches to dead man's control.



Hörmann-Your Reliable Partner for Home and Industry



1 Sectional Doors



④ Dock Levellers



7 Folding Doors



2 Rolling Shutters



(5) Dock Shelters



(8) Fire-rated Doors



③ High-speed Doors




6 Loading Houses



9 Multipurpose Doors

Hörmann: Quality without Compromise



The close-meshed network of sales and service companies throughout Europe, America and Asia makes Hörmann your strong partner for first-class building products, offering "Quality without Compromise".

Hörmann Beijing Branch

No.13 Zhong He Street, BDA, Beijing, 100176, P.R.China Tel: 010-8722 3388 Fax: 010-8722 3366 E-mail: sales.bj@hoermann.cn

Hörmann Nanjing Branch

Room 1501, Changfa Center, Building A, No.300 Zhongshan Road (E), Nanjing, 210002, P.R.China Tel: 025-8456 3629/3639/3653 Fax: 025-8456 3658 E-mail: sales.nj@hoermann.cn

Hörmann Wuhan Branch

Room A2601-2603 Zhongshang Plaza, No.9 Zhongnan Road, Wuchang District, Wuhan, 430070, P.R.China Tel: 027-8725 9041 Fax: 027-8725 9043 E-mail: sales.wh@hoermann.cn

Hörmann Changsha Branch

Room 1007, Build 1, Motianyihao Mansion, Sec.168-1 Furong Road, Tianxin District, Changsha, 410007, P.R.China Tel: 0731-8224 9890/91 Fax: 0731-8224 9892 E-mail: sales.cs@hoermann.cn

Hörmann Shanghai Branch

3/F, Qing Shui Wan Hotel Wing Office Building, No.1309 Kaixuan Road (N), Shanghai, 200063, P.R.China Tel: 021-5251 3216/5251 3217 Fax: 021-5268 1778 E-mail: sales.sh@hoermann.cn

Hörmann Xiamen Branch

Room 1607B, The Bank Centre, No. 189 Xiahe Road, Xiamen, 361001, P.R.China Tel: 0592-223 7211/8281/8171 Fax: 0592-223 7687 E-mail: sales.xm@hoermann.cn

Hörmann Chongqing Branch

Room 1605. Unit A Forebase International, 137 Keyuan 2nd Road, Jiulongpo District, Chongqing, 400039, P.R.China Tel: 023-6806 5317/5318/5320 Fax: 023-6806 5319 E-mail: sales.cg@hoermann.cn

Hörmann Shenzhen Branch

Room 301, Aokangde Building, No. 2012 Shennan Road (E). Luohu District, Shenzhen, 518001, P. R. China Tel: 0755-2515 4046/4047 Fax: 0755-2515 4049 E-mail: sales.sz@hoermann.cn

Hörmann (Hong Kong) Limited

Room 2401, 24/F, DCH Commercial Centre, No. 25 Westlands Road, Quarry Bay, Hong Kong Tel: 0852-2907 9999 Fax: 0852-2907 9666 F-mail: info@hoermann.com.hk http://www.hoermann.com.hk

Hörmann Guangzhou Branch

LOADING EQUIPMENT

HINGED DOORS

DOOR FRAMES

Room 1206. Qianshu Panfu Building, No. 233-235 Dingfeng Road (W), Yuexiu District, Guangzhou, 510180, P.R.China Tel: 020-8317 5065/5166 Fax: 020-8317 5229 E-mail: sales.gz@hoermann.cn

Hörmann Tianjin Branch

Room 1303, Tianjin City Tower, No. 35 Youyi Road, Hexi District, Tianjin, 300061, P.R.China Tel: 022-8835 6288/6289 Fax: 022-8835 6290 E-mail: sales.tj@hoermann.cn



Copyright. No part of this brochure may be reproduced without our permission. Subject to changes.

special features version. do not always represent the standard Some of the doors shown in this brochure have herefore

and t